

SKN_N0106.R15

Specific CEN Keymark Scheme Rules
for
Solar Thermal Products



Contents

SPECIFIC CEN KEYMARK SCHEME RULES	1
FOR 1	
SOLAR THERMAL PRODUCTS	1
0. INTRODUCTION	5
1. DEFINITION OF SCOPE	5
1.1 Products covered by the scheme	5
1.2 List of European Standards concerned	6
2. REQUIREMENTS AND ASSESSMENT PROCEDURES FOR BODIES ENGAGED IN CERTIFICATION, TESTING AND INSPECTION	6
2.1 Requirements for certification, testing and inspection bodies	6
3. SPECIFICATION OF THE MANUFACTURER'S APPLICATION FILE	7
4. SELECTION AND SUBMISSION OF TYPE TEST SAMPLES	7
4.1 Selection	7
4.1.1 Remote Random Sampling procedure.	7
4.2 Collector “families”	8
4.3 Custom built collectors	8
4.4 System “families”	9
4.5 Submission	9
4.6 Changes in products – re-testing	9
4.6.1 Equivalent absorbers coatings	10
4.6.2 Equivalent collector glazing	11
4.6.3 Collectors	11
5. FACTORY PRODUCTION CONTROL AND INITIAL INSPECTION OF MANUFACTURING SITE	12

6.	SURVEILLANCE	13
6.1	Surveillance test	13
6.2	Special test	13
7.	SUPERVISED MANUFACTURERS TESTING	15
8.	LIST OF BODIES FOR THE IMPLEMENTATION OF THE SCHEME.	15
9.	FEES	15
10.	ADDITIONAL REQUIREMENTS FOR OBTAINING THE LICENSE	15
11.	CHANGING CERTIFICATION BODY	15
12.	SOLAR KEYMARK CERTIFICATION OF A SYSTEM WITH A COLLECTOR CERTIFIED BY ANOTHER CERTIFICATION BODY	15
13.	CLARIFICATIONS ON SPECIFIC TESTING AND CERTIFICATION ISSUES	16
13.1	Solar Keymark certification of ICS systems	16
13.2	Negative pressure test of the collector	16
13.3	Nominal store volume	16
13.4	OEM certification	16
13.5	Hot water tapping times	16
13.6	Pre-ageing of solar collector test samples	17
	Pre-ageing of solar collector test samples	17
14.	LABELS AND LOGO	17
14.1	Display of Solar Keymark licence number on collector	17
14.2	Labelling of systems	17
15.	OTHERS	18
15.1	Mandatory identification of the manufacture	18
15.2	Translation of Solar Keymark documents	18

16. UPDATING SOLAR KEYMARK SCHEME RULES	18
17. UPDATING SOLAR KEYMARK DATABASE	18
18. REFERENCES	18
ANNEX A. SOLAR KEYMARK SURVEILLANCE TEST & SOLAR KEYMARK FACTORY INSPECTION REPORT	20
ANNEX B1. SOLAR KEYMARK COLLECTOR DATA SHEET	21
ANNEX B2. SOLAR KEYMARK SYSTEM DATA SHEET	21
ANNEX C. FEES FOR THE SOLAR KEYMARK NETWORK	22
ANNEX D. SOLAR KEYMARK SYSTEM FAMILIES	23

0. Introduction

These Specific CEN Keymark¹ Scheme Rules for Solar Thermal Products are acting as a supplement to the CEN/CENELEC INTERNAL REGULATIONS –PART 4: CERTIFICATION – 2006 [1] and CEN INTERNAL REGULATIONS - Part 3 TERMS OF REFERENCE OF THE CEN CERTIFICATION BOARD, 2006-9 [4].

Together these specific and general rules give the complete set of requirements for “Keymarking” solar thermal products covered by EN 12975, EN 12976 and EN 12977-3. Therefore, in order to get the Solar Keymark one shall follow both the general rules and these specific rules.

The basic elements/requirements of the scheme are:

- A quality system (i.e. product related factory production control) covering the production line based on the EN ISO 9000 series of standards
- Third party initial inspection of the manufacturing site (and especially the quality system management)
- Third party initial type testing sampled by independent body
- Third party periodic surveillance (i.e. periodic inspection)

The specific scheme rules are made in order to make the scheme operational for the involved parties. They are kept as close as possible to the minimum requirements for Keymark Scheme Rules as given in 4.2 of [1].

Be sure always to have the latest version of these scheme rules, available at www.solarkeymark.org.

1. Definition of scope

1.1 *Products covered by the scheme*

The scheme covers the following product main types within the work programme of CEN/TC 312 for thermal solar systems and components:

- Solar thermal collectors as defined in EN 12975
- Factory made solar thermal systems as defined in EN 12976
- Solar water heater stores as defined in EN 12977-3

¹ The Keymark is a third-party certification system on the basis of European Standards, demonstrating to users and consumers conformity to the requirements of the relevant European Standard(s). It is granted after the satisfactory completion of a certification procedure, comprising product conformity tests (initial type tests), assessment of the documented factory production control for the related production line, production site inspection and surveillance.

Collectors with different characteristics are considered as subtypes.
Systems with different characteristics are considered as subtypes.
Solar water heater stores with different characteristics are considered as subtypes.

1.2 List of European Standards concerned

The scheme refers to the normative requirements in the following European Standards:

- EN 12975: Thermal solar systems and components - Solar collectors
- EN 12976: Thermal solar systems and components - Factory made systems
- EN 12977-3: Thermal solar systems and components - Custom built systems — Part 3: Performance test methods for solar water heater stores

The scheme also refers to the procedure for calculating the output of a solar water heating system given in:

- EN 15316-4-3: Heating systems in buildings – Method for calculation of system energy requirements and system efficiencies – Part 4-3: Heat generation systems, thermal solar systems.

The standards are available from the national standardisation bodies (list of standards available see: <http://www.cen.eu/eseach/>).

2. Requirements and assessment procedures for bodies engaged in certification, testing and inspection

2.1 Requirements for certification, testing and inspection bodies

The general requirements are given in [1], part 4.1.5:

“Bodies engaged in certification, testing and inspection shall fulfil the requirements of the relevant standards for their operation, e.g. EN 45000 series and EN ISO/IEC 17000 series of standards, as well as the additional requirements defined in the Keymark scheme rules...”

The additional requirements/rules in this specific scheme are:

- The certification body in agreement with the manufacturer (license applicant) employs any of the approved testing laboratories fulfilling the requirements in this scheme and listed in paragraph 8 “List of bodies for the implementation of the scheme”.
- Evaluation of testing laboratories by the certification body is not an alternative to accreditation.
- Certification bodies, testing laboratories and inspection bodies shall participate actively in the Solar Keymark Network, i.e. participate in meetings relevant for their activities in Solar Keymark certification, testing and inspection.
- Certification bodies shall make test results public available in the harmonised format agreed upon by the Solar Keymark Network – See Annex B. Updated lists of

certified products shall be sent to the Secretariat of the Solar Keymark Network each month.

- Inspection bodies shall use the harmonised inspection procedure and checklist agreed upon by the Solar Keymark Network – Annex A.
- Certification bodies shall collect a fee for each license issued to be transferred to the Secretariat of the Solar Keymark Network. Transfer shall take place within twelve months from the date of issuing the licence. The fee for the Solar Keymark Network is given in Annex C.

3. Specification of the manufacturer's application file

The manufacturer and/or applicant shall supply the certification body with the information as required in the application form of the certification body. The application form is available from the certification body.

This information must also include the documentation required in:

- paragraph 7. “Collector identification” of EN 12975-1
- paragraph 4.6 “Documentation” of EN 12976-1
- paragraph 9.2 “Description of the store” of EN 12977-3

4. Selection and submission of type test samples

4.1 Selection

The selection of products for initial type testing is made under the responsibility of the certification body. The test samples for initial type testing are taken out of the current production or from the stock of the manufacturer. The inspector points out the test samples and records their serial numbers. The manufacturer shall prove through his factory production control and quality management system conformity of the test sample with the series production.

A series production is existing when a least 10 collectors are produced with the same materials and the same manufacturing technologies in the same way and all major production processes are performed in presence of the inspector.

At least 10 collectors of the same type more than the number of test samples picked must be available in the stock for picking the sample(s) to be tested.

SKN decision D4.M6.

4.1.1 Remote Random Sampling procedure.

The following remote sampling procedures can be used:

- Internationally operating inspection companies.
- Videosampling
- Photosampling

Detailed procedures and requirements are given in document SKN_N0126R1.

Example of: “Instructions for Completing Random Selection via Photographs is given in SKN_N0127R0 can be performed for picking samples for Solar Keymark type testing.

SKN decision D13.M8.

4.2 Collector “families”

If the manufacturer produces the “same” collector in different lengths and/or widths (i.e. the only difference between two collectors is the length and/or the width) the collector is considered the same subtype (within the same collector “family”). In this case only one sample of the smallest and one sample of the largest module shall be taken and tested². The largest module shall be subject to all the tests required in EN 12975-1 clause 5.2, and the smallest shall be subject to a thermal performance test (clause 6 of EN 12975-2)³. The performance figures used for this type shall be the performance figures corresponding to the measured instantaneous efficiency having the lowest integral in the interval of the reduced temperature⁴ from 0 – 0.1 K/(W/m²). In other words, the efficiency curve used for this subtype shall be the one embracing the smallest area.

Durability and reliability tests shall be carried out on collectors representing the major features of the collector family. E.g. collector families with collectors having several glass covers separated by bars. If the largest size of the collector - the test laboratory can test - is smaller than the smallest size of the family representing the weakest point - another testing laboratory shall carry out the respective tests - *SKN decision D2.M6*.

4.3 Custom built collectors

Custom built collectors (built in, roof integrated collectors that do not comprise factory made modules and are assembled directly on the place of installation) are handled as described in EN 12975-1, paragraph 1 “...a module with the same structure as the ready collector is tested. The module gross area in the case of custom built collectors shall be at least 2 m²”. The manufacturer has to explain the conformity of the test module with the normal production and must provide a detailed description of the components. Very large collector modules may be treated as the custom built ones, see above, if testing of the full size module is not possible.

² The module sizes are compared based on aperture area. Aperture area is defined in EN/ISO 9488. The inspector shall inspect all the different sizes of the type to verify conformity.

³ The definition of the biggest collector and the smallest collector is done at the initial test. If later a bigger size or smaller size is added to the collector family this is resulting in a new definition for the existing family. If there is a new biggest collector added this will require performance testing and reliability testing of this collector. If there is a new smallest collector added this will require performance testing on the smallest collector - *SKN decision D3.M8*.

⁴ The reduced temperature is defined in EN 12975-2, paragraph 6.1.4.8.3, and the instantaneous efficiency in 6.1.4.8.4.2.

4.4 System “families”

If the manufacturer produces the “same” system in different sizes, the different sizes of the system is considered being the same subtype (within the same system “family”). Detailed requirements for systems to be of the same subtype are given in Annex D.

Testing requirements for systems of the same subtype are:

- High temperature and safety tests (according to EN 12976) shall be performed on the sub system having the highest collector area to store volume ratio.
- All other tests (according to EN 12976 and including performance test) shall be performed on the “medium” sub system. Detailed testing requirements are given in Annex D.

Performance indicators for the system configurations which are not performance tested can be determined based on the performance test result on the “medium” system configuration according to the procedures described in Annex D.

4.5 Submission

The inspector either takes with him the test samples and delivers them to the testing laboratory, or he marks them with a permanent mark (alternatively seals their packing) and instructs the manufacturer to deliver them to the testing laboratory.

4.6 Changes in products – re-testing

The Keymark licence is not valid if a keymarked product is changed/modified. However, depending on the modifications, it might not be necessary to carry out a complete new initial type test. In order to keep the license, the manufacturer shall supply the certification body with a revised “manufacturers application file” noting that the product is a modification of an already keymarked product (specifying exactly which one) and specifying exactly which modification(s) will be made. The certification body will then assess the necessity of re-tests/supplementary tests on the basis of table C.1 in Annex C of EN 12975-1 (collectors) and table A.3 in Annex A of EN 12976-1 (systems) and taking into account decisions made at Solar Keymark Network meetings⁵. Depending on the degree of changes in the production process, the certification body will evaluate if a new initial inspection of the production line is needed. If the certification body approves the new tests (and inspection), the manufacturer may mark the modified product.

Note: The fees for the modified product are the same as for a new product, but some expenses for testing and inspection might be saved. The manufacturer may keep the license for the original product.

Note: If the changes are only changes in sub-components/materials a new initial inspection should not be necessary.

⁵ An updated list of decisions from the Solar Keymark Network meetings is available from the www.solarkeymark.org. Included here are decisions made on those specific collector and system sub-components which can be interchanged without retesting.

4.6.1 Equivalent absorbers coatings

Different coatings are considered as equivalent provided that

1. They are applied on the same substrate (e.g. copper, aluminium)
and
2. The specific test procedure described below has been passed successfully
and
3. The equality is accepted by the Solar Keymark Network

Procedure (March 2011)

If a coating is to be considered equivalent to other coatings then the following tests shall be passed and requirements shall be fulfilled:

1. Two identical collectors (apart from the absorber coating) are compared to verify the equality of the two coatings. The absorbers of the two collectors must be made of the same material and must have the same thickness. One of the collectors is coated with one of the reference coatings. The other collector is coated with the new coating.
2. The durability and reliability tests according to EN 12975-2 (being relevant with regard to the absorber, thus 5.3 High Temperature Resistance, 5.4 Exposure and 5.6 Internal Shock) for the collector with the new coating performed by an EN12975 accredited test lab are successfully passed.
3. The power curves determined by an accredited test lab for the two collectors with different coatings shall not differ by more than 2% at a temperature difference of 0 K and not more than 2% at a temperature difference of 50 K

The absorptance and emittance of the different coatings under question shall have - according to the specifications of the manufacturer - equivalent optical properties ($\alpha_1 = \alpha_2 \pm 1\%$ point at most, $\epsilon_1 = \epsilon_2 \pm 1\%$ point at most) and the same range of the production variability, e.g. $0.95 \pm 2\%$.

4. For selective absorber coatings on metal, a IEA SHC Task X test shall be performed successfully
5. The interchange ability is accepted by the Solar Keymark Network

The equivalency of the absorber coating can be challenged anytime. In this case the absorber has to be sampled by an accredited third party or by the test lab. The costs for the whole procedure are fully carried by the challenger. Upon presentation of tests that suggest none-equivalency of a absorber coating, the SKN is obliged to request the re-evaluation of a absorber coating the latest until the forthcoming SKN meeting. The absorber has to be sampled by a third party.

NB. Updated rules and procedures for exchanges of absorber coatings and updated list of absorber coatings which can be exchanged is found in latest version of SKN_N0137, public available from www.solarkeymark.org.

SKN decision D1.M5 & D5.M6 & D9.M7 & D6.M8

4.6.2 Equivalent collector glazing

Procedure (March 2011)

Collector glazing can be considered as equivalent if the following requirements are fulfilled:

- The solar transmission (AM 1,5) does not differ by more than $\pm 1\%$ from the one of the glass used for the initial Solar Keymark collector test, provided that material (including tempered/non tempered), texture, surface treatment and thickness of the glass did not change. The change in transmission must be documented with a transmission measurement made by one of the Solar Keymark test labs or by labs accredited for transmission measurements.

and

- If the glass is toughened, no additional mechanical load test is required. For other materials, a collector must be sampled according to the rules of Solar Keymark. This collector has to pass the mechanical load test according to EN 12975-2 chapter 5.8 made by one of the Solar Keymark test labs.

and

- The impact resistance test according EN12975-2, chapter 5.9 has been passed successfully with at least the same result as in the initial test (only if the impact resistance test was performed during the initial test). The tests must be carried out by a Solar Keymark test lab.

NB. Updated rules and procedures for exchanges of collector glazing and updated list of glasses which can be exchanged is found in latest version of SKN_N0138, public available from www.solarkeymark.org.

SKN decision D7.M7

4.6.3 Collectors

A collector in a Solar Keymark certified system can be changed under the following conditions:

- The original test report of the tested system configuration remains the reference for all kinds of modifications, even if a modification was accepted without retest. The procedure for an advice of amendment follows the four topics:
- The manufacturer informs the Certification Body about the planned change of collector type.
- The manufacturer delivers the test reports and Solar Keymark data sheets of both collectors and the system to the Certification Body.
- Both the Certification Body and the test lab which has issued the system test report have to approve the system modification.

A negative decision can also be based on technical consideration out of the following few requirements.

Minimum requirements on the collector:

- The alternative collector is Solar Keymark certified.
- The original collector must be performance tested according to EN 12975

- The test reports of both collectors and the system are available to the Certification Body
- The change of the collector does not cause a change of the system configuration e.g. piping, inlet connections, controller, pump etc.
- Both collectors have to be “technical identical”

Definition of “technical identical” Collector” (Data based on test report)

- Tolerance of gross area $\pm 10 \%$
- IAM (50°) $\pm 3 \%$
- The pressure drop shall not differ by more than $\pm 10 \%$ for the nominal flow rate as stated by the manufacture
- Total performance of the collector at 1000 W/m^2 :
- Integral from 0 to $100 \text{ }^\circ\text{C}$, tolerance of 0 to 10% (new collector being better than original)
- $W_{\text{peak}} \pm 10 \%$, (Peak Power [$G = 1000 \text{ W/m}^2$] per collector unit)

No modifications allowed at:

- Hydraulic flow type
- Maximal operating pressure
- Permitted heat transfer fluid

Reporting

- The original test report of the tested system remains the reference for all kinds of modifications – cascading modifications are excluded. The original test report remains unchanged and valid. The use of alternative collectors is briefly reported as an addendum to the original test report.

SKN decision D6.M7.

5. Factory production control and initial inspection of manufacturing site

With the initial inspection it is checked whether the manufacturing site fulfils the requirements stated in 4.1.3 in [1]:

“The manufacturer shall operate a quality system covering the production line of the product for which the licence to use the Keymark is granted and which should be based on the quality standards which are at least of the level of the EN ISO 9000 series of standards.

In granting the licence, the empowered certification body shall take into account the existence of any quality system certificate issued by a certification body that is accredited by a member of the European co-operation for Accreditation (EA).”

The quality management system shall cover the production line according to inspectors criteria.

The inspection procedure and checklist given in Annex A1 shall be used.

In case the manufacturer is ISO 9001 certified by a certifier accredited by a national accreditation body being a member of IAF (International Accreditation Forum) (www.iaf.nu) a Solar Keymark factory inspection is only required every second year provided the ISO 9001 report is made available to the certifier.

Based on conclusions of previous audits, interim inspections can be requested by the certifier.

SKN decision D12.M8.

6. Surveillance

The general surveillance procedures are given in 4.1.4 of [1]:

“Periodic surveillance by the empowered certification body including testing of samples from the production line or from the market and surveillance of the manufacturer's quality system.”

and A.1.6.3 of [4]:

“The factory inspections/assessments shall include the checking of the documentation of the related FPC at least once a year, as well as selecting samples for tests at least every second year ...”

6.1 Surveillance test

The surveillance test is a detailed physical inspection of the product and a comparison with the specifications of the original type tested sample. The procedure for the detailed physical inspection given in Annex A shall be used. The surveillance test shall be done at least every second year. The test samples for surveillance testing are taken out of the current production or from the stock of the manufacturer. The inspector points out the test samples and records their serial numbers. See also section 4.1.

Latest version (available from www.solarkeymark.org) of the special documents listed below shall be used for the surveillance test reports:

- SKN_N0122R0: Checks and controls for solar collectors
- SKN_N0123R0: Checks and controls made of the solar heating system

SKN decision D9.M8

6.2 Special test

Complaints concerning the conformity of a certified product are handled according to [1] section 5.4 (Complaints) and section 5.5 (Appeal procedures).

In this connection a special test can be ordered through the certification body by anyone, if the fulfilment of the requirements of the certification program or the registered values of a certified product is doubted.

The special test is normally to be made as a type test and in agreement with the manufacturer by a second approved testing laboratory listed in paragraph 8. If only one or a

few points of the certification program are challenged, the certification body decides after consulting the testing laboratory if the special test can be made as a partial or supplementary test.

If the tested product does not fulfil the requirements and/or does not comply with the registered values⁶, the legal person holding the Keymark licence of the product in question has to carry the costs of the special test.

If the tested product fulfils the requirements and complies with the registered values, the costs have to be carried by the party which questioned the fulfilment of the requirements or registered values and ordered the test through the certification body.

If the special test shows that the failure of the product to conform to the requirements and/or registered values is due to random manufacturing error or transport damage, the testing laboratory has to take a second sample. The result of this test is the obliging result for the special test.

The legal person holding the Keymark licence or a person authorised by the legal person holding the Keymark licence must have the opportunity to take part during the whole procedure of the special test. He must be informed of the results of the test without delay to have the chance to react directly.

If the special test states deviations from the requirements and/or the registered values, the certification body requires the legal person holding the Keymark licence to rectify the faults within a certain limited time which should not exceed one month, depending on the extent and manner of the fabrication. Thereafter the testing laboratory performs a new special test, the extent and manner being determined by the certification body consulting the testing laboratory.

6

- Collectors: The integral of the measured instantaneous efficiency at the special test shall be more than 90% of the already registered integral in the interval of the reduced temperature from 0 – 0,1 K/(W/m²). The reduced temperature is defined in EN 12975-2, paragraph 6.1.4.8.3, and the instantaneous efficiency in 6.1.4.8.4.2.
- Systems:
 - Solar-plus-supplementary systems: The calculated $Q_{aux,net}$ based on the special test shall be less than 110% of the originally calculated $Q_{aux,net}$. $Q_{aux,net}$ is defined in EN 12976-2, paragraph 5.9.3.2. The calculations to be compared shall be based on the Würzburg climate data and the design load already given by the manufacturer (see: EN 12976-2, Annex B, table B.1).
 - Solar-only and solar preheat systems: The calculated f_{sol} based on the special test shall be more than 90% of the originally calculated f_{sol} . f_{sol} is defined in EN 12976-2, paragraph 5.9.3.3. The calculations to be compared shall be based on the Würzburg climate data and the design load already given by the manufacturer (see EN 12976-2 Annex B, table B.1).

7. Supervised manufacturers testing

Procedures such as "supervised manufacturers' type testing" and/or "type testing at manufacturers' premises" are not included in these scheme rules.

Note: At the moment no manufacturer is doing the type testing itself. In the future it might be taken into consideration to specify the rules for such an option

8. List of bodies for the implementation of the scheme.

An updated list of empowered certification bodies and approved inspection bodies and testing laboratories is available at the Solar Keymark web site: www.solarkeymark.org.

9. Fees

By applying for the licence to use the Keymark, the manufacturer also agrees to meet:

1. the costs specified in [1]
2. the fees for the Solar Keymark Network specified in ANNEX C. These fees are not set and regulated by CEN but by the Solar Keymark network.

10. Additional requirements for obtaining the license

Some large solar collectors have to be CE-marked, further information at: <http://www.solarkeymark.org>

11. Changing certification body

Procedures for changing the certification body

- It shall be possible for a licensee to obtain a new license from another certification body without re-testing and re-inspection
- Old license shall be withdrawn when new one is issued
- Change of license should be done within 3 months after the request
The test report(s) and the inspection report(s) have to be provided to the "new" certifier
- The test institute that issued the test reports has to be accepted by the "new" certifier

SKN decision D1.M3.

12. Solar Keymark certification of a system with a collector certified by another certification body

It is no required that a system and the components in the system are Keymark certified by the same certification body. In general a certifier has to perform Solar Keymark system certification based on collector Solar Keymark certificates issued by another certification body.

The manufacturer is obliged to inform the certification body certifying his system about any changes related to the certification of the collector used in the system - including if the collector certificate is cancelled⁷.

SKN decision D4.M8.

13. Clarifications on specific testing and certification issues

13.1 Solar Keymark certification of ICS systems

Solar Keymark certification of ICS systems is possible.

SKN decision D5.M3.

13.2 Negative pressure test of the collector

“**Negative pressure test of the collector**” according to 5.9.2 EN 12975-2:2006 does not have to be performed on tubular collectors due to the following reason: The negative pressure test is intended to assess the extent to which the fixings between the collector cover and collector box are able to resist uplift forces caused by the wind. This is not relevant for tubular collectors.

There shall be a remark on the Solar Keymark certificate in case the negative pressure test was not performed as long as the pressure test is still mandatory according to the standard.

SKN decision D6.M3.

13.3 Nominal store volume

The **nominal store volume** stated on the system identification label shall not differ by more than 10 % from the effective store volume determined from the measured thermal capacity. The calculation of the percentage of the difference between the two volumes is based on the value of the effective volume. The effective store volume shall be mentioned in the test report.

SKN decision D2.M5.

13.4 OEM certification

OEM certificates shall be issued by the certifier who issued the original certificate.

SKN decision D3.M5

13.5 Hot water tapping times

Hot water tapping times

Following tapping times should be used for the performance prediction:

⁷ According to the existing rules the manufacturer is required to inform, in addition to the certifier of the collector, also the certifier of the system about any changes related to the collector. In order to be sure that the manufacturer informs the certifier of the system about a withdrawal of the certificate for the collector, it is recommended to state the obligation clearly in the contract between the certifier of the system and the manufacturer.

Table 1: Data of reference locations and adjusted tapping time.

Reference locations	Longitude ¹	Time zone	Adjustment of standard time	Tapping time (CET ²)
Stockholm	18.07°	1	-0.20	17.80
Würzburg	9.90°	1	0.34	18.34
Davos	9.82°	1	0.35	18.35
Athens	23.70°	2	0.42	18.42

Note: Time given in Table 1 are decimal figures. *SKN decision D5.M8.*

13.6 Pre-ageing of solar collector test samples

Pre-ageing of solar collector test samples

Before performing a rain penetration test the solar thermal product should be pre-aged to at least the following extent by using either possibility 1 or possibility 2:

- Possibility 1:
 - Expose the product at least for 15 valid days (according to the validity criteria of EN 12975, 5.4).
- Possibility 2:
 - Two stagnation tests using a solar simulator providing at least 850 W/m² and 10°C ambient temperature with a duration of irradiance of at least 4h. In between this two stagnation tests the collector has to reach approximately ambient temperature.
 - Exposure to outdoor conditions for at least 15 days, not requiring any boundary conditions to be fulfilled.
 - Two stagnation tests using a solar simulator providing at least 850 W/m² and 10°C ambient temperature with a duration of irradiance of at least 4h. In between this two stagnation tests the collector has to reach approximately ambient temperature.

SKN Decision D8.M10.

14. Labels and logo

14.1 Display of Solar Keymark licence number on collector

Display of Solar Keymark licence number on collector

For new Solar Keymark certificates issued from 01. May 2010 onwards it is only allowed to display the Solar Keymark logo on the collector together with the Solar Keymark licence number.

For Solar Keymark certificates issued before 01. May 2010 it is required to display the Solar Keymark licence number together with the Solar Keymark logo (in case the logo is displayed) from 01.May 2011 onwards on the collectors.

SKN decision D7.M8.

14.2 Labelling of systems

The requirement stated in EN 12976-1:2006, clause 4.7 “Every system shall have the following information durably marked on a plate or label to be visible at installation” can be considered as fulfilled if:

the label is included in the documentation supplied with the system

and

in the documentation it is stated that the label (or corresponding page of the documentation with the label) has to be placed at the systems or the site where the system is installed

and

an appropriate way for providing a durable fixing and display of the label is provided

The requirement mentioned above is relevant for the system label required according to EN 12976-1:2006, clause 4.7 and for the Solar Keymark system label.

SKN decision D3.M9.

15. Others

15.1 Mandatory identification of the manufacture

For collectors as the name of the manufacturer also the name of the supplier of the collector can be mentioned.

SKN decision D10.M7.

15.2 Translation of Solar Keymark documents

Certification bodies or test institutes can translate documents such as e.g. factory inspection reports or data sheets in other languages provided that always the original English text remain in the document.

This means that the preparation of a document using any language and English is possible.

In case of doubts, contradictions etc. the English text is the relevant one.

SKN decision D11.M7.

16. Updating Solar Keymark scheme rules

The Solar Keymark scheme rules should be updated once every year taking into account the decisions made in the meantime. Since the decisions are already agreed on by the Solar Keymark Network, no extra voting on the accordingly updated Solar Keymark scheme rules is required.

SKN decision D1.M9.

17. Updating Solar Keymark database

The certification bodies shall inform the Solar Keymark secretariat every two weeks about the Solar Keymark certificates issued and withdrawn for updating the Solar Keymark database every two weeks.

SKN decision D4.M9.

18. References

CEN/CENELEC INTERNAL REGULATIONS – Part 4: Certification – 2006

EN ISO/IEC 17025, General requirements for the competence of testing and calibration laboratories

EN 45011, General criteria for certification bodies operating product certification

[4] CEN INTERNAL REGULATIONS - PART 3 TERMS OF REFERENCE OF THE CEN CERTIFICATION BOARD, 2006-9

How to get the references:

[1] and [4] is available from CEN (www.ce.eu) and the Solar Keymark web site (www.solarkeymark.org).

[2] and [3] and the referenced standards (see section 1.2) are available from the national standardisation bodies.

ANNEX A. SOLAR KEYMARK SURVEILLANCE TEST & SOLAR KEYMARK FACTORY INSPECTION REPORT

Normative annex.

Get updated version from:

<http://www.estif.org/solarkeymark/schemerules.php>

Empowered certification body

ANNEX B1. SOLAR KEYMARK COLLECTOR DATA SHEET

Normative annex.

Get updated version from:

<http://www.estif.org/solarkeymark/schemerules.php>

Empowered certification body

ANNEX B2. SOLAR KEYMARK SYSTEM DATA SHEET

Normative annex.

Get updated version from:

<http://www.estif.org/solarkeymark/schemerules.php>

Empowered certification body

ANNEX C. FEES FOR THE SOLAR KEYMARK NETWORK

Normative annex.

Get updated version from:

<http://www.estif.org/solarkeymark/schemerules.php>

Empowered certification body

ANNEX D. SOLAR KEYMARK SYSTEM FAMILIES

Normative annex.

Get updated version from:

<http://www.estif.org/solarkeymark/schemerules.php>

Empowered certification body